



WC 130R

Heavy Duty Planetary

130,000 lb
Rated Line Pull



Features and Benefits

- 2-Year Warranty
- Fast line speed
 - Up to 16 ft/min under full load
- Oil-impregnated bronze drum bushings
 - Eliminates external drum grease zerks for less field maintenance
- Heavy-duty clutch yoke
 - Designed for easy access field maintenance
- Heavy-duty shafts
 - For strength and durability
- Symmetrical design
 - For streamline mounting
- Heavy-duty clutch splined directly to shaft
 - For strength and reliability
- 2-Speed gear motor
- SAE J706

WC 130R Specifications


Rated Line Pull (Low Speed)	130,000 lb (58,960 kg)
Weight (without Cable)	2150 lb (975 kg)
Gear Reduction	227:1

WC 130R Standard Drum							
Layer of Cable		1	2	3	4	5	6
Rated Line Pull / Layer* (Low Speed)	lb	130,000	106,300	90,000	78,000	68,800	61,500
	kg	58,960	48,210	40,820	35,380	31,200	27,890
Rated Line Pull / Layer* (High Speed)	lb	60,000	49,000	41,500	36,000	31,700	28,400
	kg	27,210	22,220	18,820	16,320	14,370	12,880
Line Speed – Low (at 60 GPM)*	FPM	16	19	22	25	28	32
	(MPM)	4.8	5.8	6.6	7.6	8.5	9.7
Line Speed – High (at 60 GPM)*	FPM	34	40	47	54	61	68
	(MPM)	10.3	12.1	14.2	16.4	18.5	20.6
Cable Capacity* Standard Drum	ft	50	110	180	265	360	465
	m	15	33	54	80	109	141

*Specifications based on recommended wire rope of 1.125 inch dia. EIPS cable and 10.3 cu. in./rev. motor at 2,600 psi working pressure and 60 gpm flow.



– Directional control valve: 3-position, 4-way motor spool.

– Winch meets SAE J706.



Performance with 10.3 in³/Rev Motor

— Low / Single Speed
- - - High / Single Speed



Wildcat Winch Series® and Ramsey Winch® are brands of Ramsey Winch Company, a wholly owned subsidiary of Ramsey Industries, Inc. Ramsey Winch reserves the right to make changes to our products without notice.